

TAURUS® 5-6
Ergänzung zur Betriebsanleitung

TAURUS® 5-6
Addition to operating manual



1431776 - 09/2018

GESIPA®

1. Technical characteristics (Amendment to para. 4.)

Type	TAURUS® 5	TAURUS® 6
Weight	3.4 kg	3.4 kg
Operating Air Pressure	5-7 bar	5-7 bar
Stroke	17 mm	15 mm
Air Supply Line Ø	6 mm	6 mm
Air consumption per fastener	approx. 6.9 NI	approx. 6.9 NI
max. pulling force at 7 bar	42,200 N	50,000 N
Hydraulic fluid Renolin Eterna 32	approx. 35 ml	approx. 31 ml
Noise emission L _{pa}	78 dB	78 dB
Vibration	<2.5 m/s ²	<2.5 m/s ²
Compressed air quality, filtered	✓	✓
Vacuum mandrel evacuation system	✓	✓
Integrated, switchable rivet suction	✓	✓

2. Current maintenance (Amendment to para. 8.)

Attention!

Never pull the trigger when no jaw mechanism is installed: This can lead to extensive damage of the tool.

3. CE Declaration of conformity (Amendment to para. 12.)

We hereby declare that the design and construction of the tool named below, as well as the version that we have put on the market, complies with applicable fundamental health and safety requirements stipulated in EU directives. Tool modifications made without our authorization shall render this declaration void. The safety information in the product documentation provided must be observed. This document must be retained.

TAURUS® 5-6

- 2006/42/EG
- DIN EN ISO 12100:2011
- DIN EN ISO 11148-1:2012
- DIN EN 82079-1:2013